

三久 米麥兩用·蔬菜種子水份計

SUNCUE MOISTURE TESTER



米麥兩用水份計

TD-6 FOR
PADDY AND WHEAT



蔬菜種子水份計

VS-6 FOR
VEGETABLE SEEDS

特點

- **清楚易懂**
大型液晶顯示，清楚易懂。
- **操作簡單**
操作按鈕少，可防止錯誤發生。
- **自動水分換算機能**
只要按穀物選擇按鈕，各種穀物/蔬菜種子的水份，均可自動換算。
- **平均值計算機能**
只要按平均值按鈕，就可計算2~9次的平均值。
- **溫度補正機能**
採用特殊電子迴路自動溫度補正裝置。
- **自動斷電機能**
經過一分鐘以上沒有操作時，電源會自動切斷。

FEATURES

- **Clear and easy to understand**
Large, easy-to-read LCD display.
- **Simple operation**
Simple button design to prevent errors.
- **Mode conversion**
Press "select" button to convert measurement to various grain and vegetable seeds.
- **Average calculation**
Press "average" button to get average moisture content from 2 to 9 entries.
- **Temperature compensation**
Unique electronic circuit can do temperature compensation automatically.
- **Power off automatically**
After one minute without operating, power will shut off automatically.

三久米麥兩用/蔬菜種子水份計-機能豐富、操作簡單、防止過度乾燥

SUNCUE Computerized Moisture Tester-multiple functions, simple operation, prevents overdrying.

● 附攜帶型收納盒 Portable case



● 操作簡單的TD-6/VS-6 Simple operation



1 按壓**測定**鈕
電源開關
Press **MEASURE** key
power switch



2 按壓**選擇**鈕▶選擇穀物
Press **SELECT** key
▶to select grains



3 試料盤插入測定部
Insert the sample tray
into measuring part



4 旋轉測定把手
Rotate the handle



5 按壓**測定**鈕，顯示水份值
Press **MEASURE** key
to display the result

規格 SPECIFICATIONS

項目Item	機型Model	TD-6	VS-6
測定對象及範圍 Application & Measuring range	稻穀 Paddy	8.7~40.0%	大麥 Barley 8.0~34.3%
	糙米 Brown rice	9.1~40.0%	小麥 Wheat 8.6~35.0%
	白米 Polished rice	9.8~20.0%	裸麥 Rye 8.4~34.7%
顯示解析度 Resolution		0.1% 但是30%以上以1%為量測單位 moisture content above 30% will be rounded off to the nearest integer	
測定精度 Accuracy		±0.5%, 10~20%	
使用溫度範圍 Operating temp. range		5~40°C 結露除外 exception for dewing	
顯示方式 Display		大型液晶數字顯示	LCD digital display
溫度補正 Temp. range of material		自動補正	automatically compensates for temperature
電源 Power		3號乾電池, 1.5V*4只	four No.3 "AA" batteries 1.5V
換算方式 Calculation		以微電腦自動換算	moisture automatically converted by micro-computer
本體尺寸 Dimensions		長172×寬100×高75 mm	L172×W100×H75 mm
重量 Weight		約500g	about 500g

- 測定注意事項：本水份計採用日本檢量線，會因地區性、大氣溫度、相對溼度、穀物品種之不同，所測得之水份會有誤差。所以請依當地的國家標準，例如絕乾法：5g粉碎的穀物，放入105°C的恆溫箱，烘乾5小時的作業方法，在當地做出檢量線，或配合當地糧管單位的水份計和本水份計做出對照表，再施行測定作業，顯示出的水份值再看對照表的實際水份值，即為穀物的正確含水率。
- 圖示及規格僅供參考，實際產品規格以客戶簽署訂單及出貨實物為主。
- Notice to measurement: The moisture content will be different because of region, ambient temperature, relative humidity and grain types. Please make calibration according to the national standard. Such as oven-dry method: by putting 5g of ground grain in an oven, drying at 105°C for 5 hours or make tabulation table by comparing the moisture content tested from the local Food Administration. Referring to the tabulation table to obtain the accurate grain moisture content.
- The specification and graph is for reference only. Actual specification of SUNCUE product shall be based on the Sales Confirmation which customers sign and delivered products.

SUNCUE
三久股份有限公司
SUNCUE COMPANY LTD.

41348台中市霧峰區民生路396號
No.396, Minsheng Rd., Wufeng Dist., Taichung City 41348, Taiwan, R.O.C.
Tel +886-4-2339-7171 Fax +886-4-2330-2939
Website www.suncue.com
E-mail sales@suncue.com



服務中心 Service Center