

썬큐조선키

SUNCUE PRE-CLEANER

원료곡에 포함된 이물질을 제거, 건조기에 투입하여 건조속도를 높이고,
기름과 전기를 절감하며, 건조기에서 균일하게 건조할 수 있도록 합니다

Enhance drying evenness, increase loading capacity and drying efficiency.
Power and fuel saving, and reduce uneven moisture.



SPC-50

제품사양 SPECIFICATIONS

항목 Item		모델 Model	SPC-15	SPC-50
선별방식	Function		풍력선별+진동선별 Winnow and Sieve	
적용곡물	Application		벼. 밀. 보리. 옥수수 등 Paddy, Wheat, Barley, Corn etc.	
외부규격 폭×길이×높이mm	Dimension	L×W×H mm	2,173×1,853×1,756	2,918×2,370×3,278
무게 kg 약	Net Weight	Approx. kg	900	2,200
처리능력 톤/시간	Capacity	ton/ hr	5~15	20~50
사용전원	Voltage		3상, 220V/380V/415V/440V, 50/60Hz	
소요동력 kW	Power Consumption	kW	3	7.87

- 본 도면 및 규격은 참고 용이며, 실제의 사양은 견적서를 참조하세요.
- 처리량은 일본 콤바인을 이용하여 수확하는 곡물량이고, 실제 데이터는 혼입율이나 곡물 수분에 따라서 달라 질 수 있습니다.
- 스탠드, 유지보수 작업대, 버퍼 탱크 등 선택사항입니다.
- Stand, maintenance platform, inlet hopper, outlet hopper and air pipe are optional.
- The specification and graph are for reference only. Actual specification of SUNCUE product shall be based on the Sales Confirmation which customers sign and delivered products.
- The handling capacity is based on using Japanese combine harvester. If impurity rate and moisture content are too high, then the actual handling capacity might be lower than listed.



특장점 FEATURES

- 산물버 품질에 따라 처리량 조정 가능
- 1차 풍력선별 후 2차 진동선별
- 상·하부 동시 2단 진동선별, 처리량 2배 증대
- 콤팩트한 설계로 최소의 설치면적
- 진동선별 전·후 2번에 걸친 풍력선별
- Pre-cleaning speed can be adjusted according to wet grain quality.
- High purity after pre-cleaning thanks to winnowing and sieving.
- Dual screens work simultaneously to increase capacity.
- Saves space.
- Dual winnowing at grain entry and exit.

공급처 INSTALLATION



김제 원예농협 Korea



천안 동천안농협 Korea



철원 동송농협 Korea



아산 푸른들 영농 Korea

SUNCUE
선큐 곡물 건조기
SUNCUE COMPANY LTD.

타이중시 대리구 인화로 105호

No. 105, Renhua Rd., Dali Dist.,
Taichung City 412039, Taiwan, R.O.C.

☎ +886-4-2339-7171

🌐 www.suncue.com



☎ +886-4-2330-2939

✉ sales@suncue.com

대리점 Service Center